


# ATS608

# Plug-in input expander, 8-way

### 8-way plug-in input expander

The ATS608 offers 8 zone input expansion to Axon and Advisor Advanced panels. To reduce required space in the Main control panel housing, the unit is a plug-in to the Main Control panel PCB. The ATS608 provides for 8 additional inputs available through screw terminals. Inputs are assigned to zones through configuration in the control panel. The zone type is defined through the zone menu in the main control panel.



#### **Details**

- 8 zone inputs
- Plug-in to Axon and Advisor Advanced panels
- Supports shock sensors

# ATS608 Plug-in input expander, 8-way

## **Technical specifications**

General			
Expander type		Input expander	
Product line		Advisor Advanced, Axon	
Connection type		Plug-in	
Max. distance from panel		Locate	d on the panel PCB
Max. per panel		1	
Inputs			
Total		8	
Onboard		8	
Electrical			
Operating voltage		10.5 to 13.8 VDC	
Current consumption		10 mA	
Physical			
Physical dimensions		80 x 35 mm	
Environmer	ntal		
Operating temperature		0 to +50°C	
Relative humidity		95% noncondensing	
Environment		EN50130-5 ; Class II - Indoor (general)	
Regulatory			
Certification		EN50131 Grade 3, VdS	
Compatible	produc	ts	
Category	Reference		Description
Control Panel	ATS170	00-MBC	AXON 1700 PCB replacement board
Control Panel ATS1700-MM		00-MM	Axon 1700 security panel, IP-onboard, EN grade 3, WebApp, 8 onboard zones max 32 zones, 4 areas, medium metal housing, multi-lingual
Control Panel ATS3700-N		00-MBC	AXON 3700 PCB replacement board
Control Panel	ATS3700-MM		Axon 3700 security panel, IP-onboard,

EN grade 3, WebApp, 16 onboard zones max 256 zones, 16 areas, medium metal housing, multi-lingual



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.