

# DM880

880 Series Push Button Activated Manual Call Point In Plastic Housing (Red)

## General

The DM880 is a RED, push-button-activated manual call point. It is supplied in a robust ABS housing and is suitable for indoor surface mounting. The door features a replaceable break glass and allows for an automatic reset when opening and closing the door.

It is supplied with the "House on Fire" functional marking, is EN54-11 certified and conforms to DIN14655.



## Standard Features

- EN54-11 approved, push-button-activated MCP
- Robust ABS housing
- "House-on-Fire" functional indicator
- Automatic reset when opening/closing the door
- VdS approved

# DM880

## 880 Series Push Button Activated Manual Call Point In Plastic Housing (Red)

### Specifications

Physical	
Physical dimensions	125 x 125 x 36 mm (W x H x D)
Net weight	225 g
Colour	Red (RAL 3001)
Environmental	
Operating temperature	-40 to +80°C
Environment	Indoor
IP rating	IP42
Standards & regulation	
Certification	EN54-11
Power supply	
	12 to 24 VDC
Current consumption	
	7 mA
Operating temperature	
	-40°C to 80°C
IP rating	
	IP42
Door opening angle	
	>180°
Material	
	PA6 + 30%GF
Size (w x h x d)	
	125 x 125 x 36 mm
Colour	
	Red, RAL3001
Weight	
	225g

### Ordering Information

Part No.	Description
DM880	880 Series Push Button Activated Manual Call Point In Plastic Housing (Red)
DM900KEY	Replacement Key For DM880/980 Series Manual Call Points
DM966	Replacement Clear Windows For Push-Button-Activated Manual Call Points