

## HYU-899

SF-XVR6108-1FACE

HYUNDAI

### ZVR 5 in 1 8ch HDCVI / HDTVI / AHD / CVBS + 2ch IP 6MP



HDCVI™

HDTVI

AHD

CVBS

H.265+

ai**sense**



MOTION  
DETECTION 2.0



- ZVR 5 in 1 with 8 channels HDCVI / HDTVI / AHD / CVBS + 2 channels IP 6MP
- Video format H.265 +, H.265, H.264 +, H.264
- Two-way audio
- 8 channels of audio through coaxial
- 8-channel synchronized playback
- Recording 4M-N, 3MP, 1080P, 1080P Lite, 720P, 720P Lite, WD1, 4CIF, VGA, CIF
- HDMI and VGA outputs at 1080P
- Motion detection 2.0
- 4-channel perimeter protection with human / vehicle analysis
- 1 HDD SATA capacity up to 10TB
- RJ45 Fast Ethernet
- Onvif, P2P, DDNS
- RS485, 2 USB2.0
- 12V DC.



#### Reference / Model

HYU-899 / SF-XVR6108-1FACE

8-channel 5-in-1 ZVR format H.265 +, H.265, H.264 +, H.264

5 technologies: IP cameras, HDCVI, HDTVI, AHD and analog CVBS

8 BNC inputs (supports coaxitron):

HDTVI: 4MP @ 25 ips, 3MP @ 18 ips (channels 1 and 2 only), 1080P @ 25 ips, 720P @ 25/50 ips

HDCVI: 4MP, 1080P, 720P @ 25 ips

AHD: 4MP, 1080P, 720P @ 25 ips

CVBS: Analog: 960H

Normal IP: 2 IP inputs (up to 10 inputs bypassing BNC) at 6MP

Enhanced IP: 4 IP inputs (up to 12 inputs bypassing BNC) at 4MP

Simultaneous HDMI and VGA (1080P) outputs

BNC output (1.0 Vp-p)

Two-way audio

1 RCA input / 1 RCA audio output

**ZVR 5 in 1 8ch HDCVI / HDTVI / AHD / CVBS + 2ch IP 6MP**

Reference / Model	HYU-899 / SF-XVR6108-1FACE
	8 channels of audio over coaxial
	Recording resolution: 4M-N, 3MP, 1080P, 1080P Lite, 720P, 720P Lite, WD1, 4CIF, VGA, CIF
	Main stream with 1080P Lite mode disabled:
	Stream 4MP: 4M-N (15 ips), 1080P Lite, 720P, WD1, 4CIF, VGA, CIF (25 ips)
	Stream 3MP: 3MP, 1080P, 720P, VGA, WD1, 4CIF, CIF (15 ips)
	Stream 1080P: 1080P, 720P (15 ips), VGA, WD1, 4CIF, CIF (25 ips)
	Stream 720P: 720P, VGA, WD1, 4CIF, CIF (25 ips)
	Main stream with 1080P Lite mode activated:
	4M-N, 3MP (15 ips), 1080P Lite, 720P Lite, WD1, 4CIF, VGA, CIF (25 ips)
	Secondary stream: WD1, 4CIF (12 ips), CIF (25 ips)
	8-channel synchro playback
	Motion detection with people / vehicle analysis: Deep learning based motion detection 2.0 is enabled by default for all analog channels, it can classify people and vehicles, and greatly reduce false alarms caused by objects such as leaves and lights; Quick search by object or event type is supported
	Up to 4 perimeter protection channels with human / vehicle analysis
	Internal capacity for 1 SATA HDD up to 10TB (sold separately)
	Self-adaptive RJ45 (10 / 100M) Ethernet network interface
	Network protocols: TCP / IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS
	ONVIF compliant
	Remote access for up to 64 users
	Connectable to Wifi network via Wifi dongle via USB interface
	Remote access through iPhone / iPad, Android devices
	Multi browser compatibility: Chrome, Firefox, Safari, IE
	P2P in the cloud, DDNS DEMES, Push and channel zero
	RS48 half-duplex port
	2 USB 2.0 ports
	Power supply: 12V DC, 1.5A

**HYU-899**

SF-XVR6108-1FACE

**HYUNDAI**

**ZVR 5 in 1 8ch HDCVI / HDTVI / AHD / CVBS + 2ch IP 6MP**

Reference / Model	HYU-899 / SF-XVR6108-1FACE
Consumption: ≤18W	
Operating temperature: -10 ° C ~ + 55 ° C	
Relative humidity: 10 ~ 90%	
Dimensions: 315 × 242 × 45mm	
Weight: ≤1.78 kg	