

AS363

Conventional fire sounder, multi tone with shallow base

General

The AS363 is a general purpose electronic sounder for fire alarm applications. Which features a special base containing all wiring connections and allow for easy removal/placement of the sounder.

Easy and fast installation

The AS363 alarm sounder allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these sounders use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The AS363 provide high sound output at a low current, thus reducing power requirements and system cost. The AS363 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second tone, is available if extra wires are installed in the sounder circuit.

The mechanism for locking the sounder to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Details

- High sound output
- Low current consumption
- 32 Tones user selectable
- Automatic synchronisation
- Volume control
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- Two stage alarm
- VdS Approved

AS363

Conventional fire sounder, multi tone with shallow base

Technical specifications

General

Line monitoring	polarised input
-----------------	-----------------

Electrical

Operating voltage	17 to 60 VDC (EN54-3 / fire applications) 9 to 60 VDC (non-fire applications)
-------------------	--

Current consumption	4 to 41 mA @ 24 VDC
---------------------	---------------------

Sounder

Output level	94 to 106 dB(A) (at 1 m) Continuous
--------------	--

Selectable tones	32
------------------	----

Synchronization	Phased start (automatic synchronisation)
-----------------	--

Physical

Physical dimensions	100 x 81 mm (Ø x H) (shallow base)
---------------------	------------------------------------

Net weight	215 g
------------	-------

Colour	Red
--------	-----

Material	High impact polycarbonate
----------	---------------------------

Environmental

Operating temperature	-25 to +70°C
-----------------------	--------------

Environment	Indoor
-------------	--------

IP rating	IP21
-----------	------

Regulatory

Certification	EN54-3
---------------	--------

Compatible products

Category	Reference	Description
Notification device	AS363W	Conventional fire sounder, multi tone with shallow base
Notification device	AS364	Conventional fire sounder, multi tone with deep base
Notification device	AS364W	Conventional fire sounder, multi tone with deep base
Notification device	AS36RIM	Sounder Beacon Rim With "Fire" Text (English)
Notification device	AS36RIM-09	Sounder Beacon Rim With "Fuego" Text (Spanish)



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 September 2024 - 11:16